

* Material Safety Data Sheet *

SECTION 6 - HEALTH HAZARD DATA

Exposure effects - Acute symptoms may occur.

Threshold limit value - OSHA permissible exposure limit not established.

Ingestion - Low toxicity if swallowed.

Inhalation - Low toxicity if inhaled.

Skin - Molten material will produce thermal burns if it is allowed to come in contact, or absorbed through skin.

Eye - May cause minimal irritation if allowed to come in contact with the eye area.

Chronic - No specific information.

Emergency and First Aid procedures

Eye contact - Flush with water to remove particles.

Skin contact - If molten material contacts skin, cool rapidly with cool water.

Ingestion - If a significant quantity has been swallowed, give two glasses of water to induce vomiting. Never give anything to an unconscious person.

Inhalation - Remove to fresh air. If breathing is difficult, give oxygen.

Seek medical attention for all above occurrences.

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USAGE

Released or spilled material - Pellets are slippery, sweep up and place in a disposable container.

Waste disposal method - Incinerate or bury in landfill in accordance with federal, state, and local regulations. Waste material should be reviewed to determine the applicable hazards. This product should be tested for EP.

Handling and storage - Do not store near acids. Keep containers closed and wash hands thoroughly after handling.

SECTION 8 - CONTROL MEASURES

Respiratory protection - None needed.

Ventilation - Low exhaust is recommended when appropriate to control employee exposure.

Mechanical may not be adequate as the sole means to control employee exposure.

Protective equipment - Chemical goggles are recommended. Protective gloves are recommended during processing. Body protection is necessary to prevent skin contact.

* Material Safety Data Sheet *

SECTION 9 - FEDERAL AND STATE REGULATIONS

SECTION 313 NOTIFICATION

This product may contain toxic chemicals pertaining to the reporting requirements of Section 313, of the Sara Title 3 of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR Part 372.

Section 313 of Sara Title 3 requires this information to be attached to the material safety data sheet for this product.

<u>CHEMICAL NAME</u>	<u>CAS#</u>
Titanium Dioxide	13463-67-7
Metal Salt Azo Yellow	129423-54-7
C.I. pigment yellow 214/Organic	Proprietary
Zinc Stearate	557-05-1
Polypropylene	9003-07-0

State Regulations

The state of California regulation (proposition 65) identifies specific chemicals known to cause cancer or birth defects. Proposition 65 requires a disclosure for products sold within the state of California containing an identified chemical. The following disclaimer is required by the state of California: This product may contain chemicals known to the state of California to cause cancer or birth defects.

Data provided in this MSDS was obtained from evaluation studies by pigment, dye, and thermoplastics resin suppliers as well as literature references. As we believe this information to be accurate and reliable to the best of our knowledge, it is the responsibility of the user to request updated information on this specific product. Since conditions of use are beyond our control, we make no warranties, expressed or implied with respect to the information contained herein.